




 <b>19</b> <b>INLES d.d.</b> Kolodvorska 22 SI-1310 Ribnica SLOVENIJA
<b>INO-KF Living MD TopAlu – 01</b> IN12431/0  <b>EN 14351-1:2006+A2:2016</b>  <b>Single casement PVC window</b>  for build in vertical wall openings of the buildings without resistance to fire  Air permeability <b>class - C3/B3</b> Watertightness <b>class - 9A</b> Resistance to wind load <b>class - 4</b> Thermal transmittance $U_w$ <b>1,2 W/m<sup>2</sup> K</b>
notified Body: IFT Rosenheim Gmbh Theodor-Gietl Str. 7-9 83036 Rosenheim, Germany (NB-Nr. 0757)

 <b>19</b> <b>INLES d.d.</b> Kolodvorska 22 SI-1310 Ribnica SLOVENIJA
<b>INO-KF Living MD TopAlu – 06</b> IN12431/1  <b>EN 14351-1:2006+A2:2016</b>  <b>Double casement PVC window (symmetric)</b>  for build in vertical wall openings of the buildings without resistance to fire  Air permeability <b>class - C2/B3</b> Watertightness <b>class - 9A</b> Resistance to wind load <b>class - 4</b> Thermal transmittance $U_w$ <b>1,2 W/m<sup>2</sup> K</b>
notified Body: IFT Rosenheim Gmbh Theodor-Gietl Str. 7-9 83036 Rosenheim, Germany (NB-Nr. 0757)

 <b>19</b> <b>INLES d.d.</b> Kolodvorska 22 SI-1310 Ribnica SLOVENIJA
<b>INO-KF Living MD TopAlu – 07</b> IN12431/2  <b>EN 14351-1:2006+A2:2016</b>  <b>Double casement PVC window (asymmetric)</b>  for build in vertical wall openings of the buildings without resistance to fire  Air permeability <b>class - C2/B3</b> Watertightness <b>class - 9A</b> Resistance to wind load <b>class - 4</b> Thermal transmittance $U_w$ <b>1,2 W/m<sup>2</sup> K</b>
notified Body: IFT Rosenheim Gmbh Theodor-Gietl Str. 7-9 83036 Rosenheim, Germany (NB-Nr. 0757)

 <b>19</b> <b>INLES d.d.</b> Kolodvorska 22 SI-1310 Ribnica SLOVENIJA
<b>INO-KF Living MD TopAlu – 08</b> IN12431/3  <b>EN 14351-1:2006+A2:2016</b>  <b>Fixed PVC window</b>  for build in vertical wall openings of the buildings without resistance to fire  Air permeability <b>class - C3/B3</b> Watertightness <b>class - 9A</b> Resistance to wind load <b>class - 4</b> Thermal transmittance $U_w$ <b>1,2 W/m<sup>2</sup> K</b>
notified Body: IFT Rosenheim Gmbh Theodor-Gietl Str. 7-9 83036 Rosenheim, Germany (NB-Nr. 0757)

 <b>19</b> <b>INLES d.d.</b> Kolodvorska 22 SI-1310 Ribnica SLOVENIJA
<b>INO-KF Living MD TopAlu – 11</b> IN12431/5  <b>EN 14351-1:2006+A2:2016</b>  <b>single casement PVC balcony door</b>  for build in vertical wall openings of the buildings without resistance to fire  Air permeability <b>class - C3/B3</b> Watertightness <b>class - 9A</b> Resistance to wind load <b>class - 4</b> Thermal transmittance $U_w$ <b>1,2 W/m<sup>2</sup> K</b>
notified Body: IFT Rosenheim Gmbh Theodor-Gietl Str. 7-9 83036 Rosenheim, Germany (NB-Nr. 0757)

 <b>19</b> <b>INLES d.d.</b> Kolodvorska 22 SI-1310 Ribnica SLOVENIJA
<b>INO-KF Living MD TopAlu – 12</b> IN12441/6  <b>EN 14351-1:2006+A2:2016</b>  <b>double casement PVC balcony door (symmetric)</b>  for build in vertical wall openings of the buildings without resistance to fire  Air permeability <b>class - C2/B3</b> Watertightness <b>class - 8A - 9A</b> Resistance to wind load <b>class - 4</b> Thermal transmittance $U_w$ <b>1,2 W/m<sup>2</sup> K</b>
notified Body: IFT Rosenheim Gmbh Theodor-Gietl Str. 7-9 83036 Rosenheim, Germany (NB-Nr. 0757)

\* This value refers to the glazing with  $U_g = 1,1 \text{ W/m}^2\text{K}$ .



19  
**INLES d.d.**  
 Kolodvorska 22  
 SI-1310 Ribnica  
 SLOVENIJA

**INO-KF LivIng MD TopAlu – 13**  
 IN12441/7

**EN 14351-1:2006+A2:2016**

**double casement PVC  
 balcony door (asymmetric)**

for build in vertical wall openings of the  
 buildings without resistance to fire

Air permeability **class - C2/B3**  
 Watertightness **class - 8A -9A**  
 Resistance to wind load **class - 4**  
 Thermal transmittance  $U_w$  **1,2 W/m<sup>2</sup> K**\*

notified Body:  
 IFT Rosenheim Gmbh Theodor-Gietl Str. 7-9  
 83036 Rosenheim, Germany (NB-Nr. 0757)



19  
**INLES d.d.**  
 Kolodvorska 22  
 SI-1310 Ribnica  
 SLOVENIJA

**INO-KF LivIng MD TopAlu – 14**  
 IN12441/8

**EN 14351-1:2006+A2:2016**

**sliding PVC balcony door  
 (PSK)**

for build in vertical wall openings of the  
 buildings without resistance to fire

Air permeability **class - C3/B3**  
 Watertightness **class - 9A**  
 Resistance to wind load **class - 4**  
 Thermal transmittance  $U_w$  **1,2 W/m<sup>2</sup> K**\*

notified Body:  
 IFT Rosenheim Gmbh Theodor-Gietl Str. 7-9  
 83036 Rosenheim, Germany (NB-Nr. 0757)

\* This value refers to the glazing with  $U_g = 1,1 \text{ W/m}^2 \text{ K}$ .